PATENT ABSTRACTS OF JAPAN

(11)Publication number:

08-096429

(43)Date of publication of application: 12.04.1996

(51)Int.CI.

G11B 11/10 G11B 11/10

(21)Application number: 06-227854

(71)Applicant: TEIJIN LTD

(22)Date of filing:

22.09.1994

(72)Inventor: SHINTAKU KAZUHIKO


(54) MAGNETO-OPTICAL RECORDING MEDIUM

(57)Abstract:

PURPOSE: To improve the quality of a reproduced signal by transferring information recorded in a recording layer to a readout layer excellent in reproducing performance and reproducing the information from the

readout layer.

CONSTITUTION: A discoid polycarbonate resin substrate is used as a substrate 1, an AlSiN film is formed as a 1st transparent dielectric layer 2 and a readout layer 3 is formed using a discoid GdFeCo alloy as a target. A recording layer 5 is then formed using a discoid TbFeCo alloy as a target. The layers 5, 3 are formed as a magnetically coupled multilayered film and a middle layer 4 of a nonmagnetic alloy consisting of at least one among Cu, Au, Ag, Pt and Pd and at least one among V, Cr, Mn, Zn, Y, Zr, Mo, Ru, Rh, Sn, W, Re, Pb, Fe, Co, Ni and Gd and Tb as magnetic rare earth metals is interposed between the magnetic layers. Information recorded in the recording layer 5 is transferred to the readout layer 3 and this information is satisfactorily reproduced from the readout layer 3.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office